


[On Line Catalog](#)


BURNDY Catalog Number YA36LTC38FX
UPC Number 7818101014144
Description CU HYLUG-450 FLEX-3/8STD
Status Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	3.23
Height (in)	1.19
Barrell Style	Chamfered
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.27
B Length (in)	1.38
Pad Width (in)	1.74
Strip Length	1-3/8

General

Number of Holes	1
Product Description	Cu Comp Terminal Flex Cond, Bvl Entry, 1 Hole/W/InspWindow, 444.4 kcmil(1100/#24)DLO, 450 kcmil Flex, 600 V-35 kV, 3/8" Stud, Std bbl

Conductor(s)

Flex (Class G) Size - Range	450 kcmil
Flex (Class H) Size - Range	450 kcmil
Flex (Class I) Size - Range	450 kcmil
Copper Solid Size (Range)	N/A
DLO Size (Range)	444.4 (1100/#24) DLO
Copper Stranded (Range)	N/A

Physical

Type of Plating	Tin
Bolt Hole Size	3/8
Color Code	Brown
Plated (Yes or No)	Y
Index Number	20,299
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

BURNDY Technical Services

Hours: 8:00 AM - 5:00 PM
 Monday - Friday

5/30/2018

Datasheet - Burndy - YA36LTC38FX

47 East Industrial Park Drive
Manchester NH 03109

47 East Industrial Park Drive
Manchester NH 03109

Phone: 800-346-4175