




BURNDY Catalog Number
UPC Number
Description
Status

YA38L2NNTFX
 7818100347433
 CU HYLUG-500FLEX-NARROW-
 Active

Web Use
 BURNDY Product Line



Dimensional

Tongue Angle	Straight
Length (in)	5.35
Barrell Style	Chamfered,Skived
Bolt Hole Size (in)	0.52
Barrel Type	Standard
Thickness	0.27
B Length (in)	1.45
Pad Width (in)	1.63
E - in	1.75
Strip Length	1-7/16

General

Number of Holes	2
Product Description	Flex Conductor Standard Barrel Narrow, 535.3 kcmil 1325/24 500 Flex, 1/2 in, 5.35 in L

Conductor(s)

Flex (Class G) Size - Range	500 kcmil
Flex (Class H) Size - Range	500 kcmil
Flex (Class I) Size - Range	500 kcmil
Copper Solid Size (Range)	N/A
DLO Size (Range)	535.3 (1325/#24) DLO
Copper Stranded (Range)	N/A

Physical

Type of Plating	Tin - Electro Plated
Bolt Hole Size	1/2
Color Code	Pink
Plated (Yes or No)	Y
Index Number	L99
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175