



BURNDY Catalog Number
UPC Number
Description
Status

YA39A5N131TD12E
 7818102903099
 ALLUG-750KCM-NEMA-NARTNG
 Active

Web Use
 BURNDY Product Line

Dimensional

Length (in) 6.09
 Bolt Hole Size (in) 0.52
 Thickness 0.31
 B Length (in) 1.86
 Pad Width (in) 1.31
 E - in 1.75
 Strip Length 1-7/8

General

Number of Holes 2
 Product Description Cu & Al Compression terminal, 2 Holes/W/in sp W, 500-900 kcmil Al 500 kcmil for Cu only, 600V-35Kv, 1/2" stud, Pink, 300 Index, Narrow tongue terminal

Conductor(s)

Flex (Class G) Size - Range N/A
 Flex (Class H) Size - Range N/A
 Flex (Class I) Size - Range N/A
 Copper Solid Size (Range) N/A
 DLO Size (Range) N/A
 Copper Stranded (Range) 500 kcmil

Physical

Type of Plating Tin - Electro Plated
 Bolt Hole Size 1/2
 Color Code Pink
 Plated (Yes or No) Y
 Index Number 300
 Product Material Aluminum

Approvals / Certifications

UL Listed Y
 CSA Certified Y
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175