BURNDY

L	BURNDY Catalog Number UPC Number Description Status Web Use BURNDY Product Line	YDS75 7818105648066 1/0 SLD CU FULL TEN SPLI Active
	Discussional	
		nsional
	B Length (Fraction)	2-5/6
	Length (in)	5.93
	B Length (in)	2.84
	Length (Fraction)	6-1/4
		neral
		Copper splice designed to develop
B	Product Description	full rated breaking strength of hard drawn and medium hard drawn solid copper conductor. ANSI C119.4 Class 1 (Full Tension),Die index:165
	Prefilled (Oxide Inhibitor)	Y
	Conductor(s) Aluminum Coated Steel Size (Range) N/A	
	Copper Solid Size (Range)	1/0 AWG
	Galvanized Steel Size (Range)	N/A
	Copperweld Solid Size (Range)	N/A
	Copper Stranded (Range)	N/A
	CopperWeld Stranded Size (Range)	N/A
	Phy	ysical
	Type of Splice	Full Tension Sleeve
	Index Number	165
	Approvals / Certifications	
	UL Listed	Ν
	CSA Certified	Ν
	ROHS Compatible	Compliant
	UL Recognized	N
	CULUS	Ň
	Documentation	
	For further technical assistance, please co	ntact us
BURNDY LLC - USA	BURNDY Technical Services	Hours: 8:00 AM - 5:00 PM Monday - Friday Phone: 800-346-4175
		Phone: 800-346-41/5

47 East Industrial Park Drive Manchester NH 03109

47 East Industrial Park Drive Manchester NH 03109

Phone: 800-346-4175