




BURNDY Catalog Number YGL34C2
UPC Number 7818102200300
Description 250-500 TO 2-250 GRD
Status Active



Web Use
 BURNDY Product Line



Length (in) 2.50
 B Length (in) 0.75

Dimensional

2.50
 0.75

General

Product Description

Hygrid Cross Connector, #6 solid through 500 kcmil, 2.50 in L, 2.09 in W

Prefilled (Oxide Inhibitor)

Y

Type of Oxide Inhibitor

Other

Penetrox E

Approvals / Certifications

Rated for Direct Burial

Y

UL Listed

Y

CSA Certified

Y

ROHS Compatible

Compliant

UL Recognized

N

CULUS

N

Industry Standards

UL467,IEEE 837

Conductor(s)

Rod Size (Side A) - Range

5/8 in-3/4 in

Rod Size (Side B) - Range

N/A

Rebar Size (Side B) - Range

N/A

Copper Solid Size (Side A) - Range

N/A

Copper Str Size(Side B) - Range

6 AWG-2 AWG

Copper Str Size (Side A) - Range

250 kcmil-500 kcmil

CopperSolid Size (Side B) - Range

N/A

Rebar Size (Side A) - Range

5 -6

Physical

Type of Plating

Unplated

Plated (Yes or No)

N

Index Number

998

Product Material

Copper

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM

Monday - Friday

Phone: 800-346-4175