



BURNDY Catalog Number
UPC Number
Description
Status

YGLR29C58
 7818102208188
 2-250 GRD GRID TO 5/8 RO
 Active

Web Use
 BURNDY Product Line

Length (in)
 B Length (in)
 D - in
 BB - Length (in)
 B Length (Fraction)

Dimensional
 2.53
 0.75
 0.31
 0.88
 3/4

Product Description
 Prefilled (Oxide Inhibitor)
 Type of Oxide Inhibitor

General
 Copper Compression Connector,
 Ground Rod to Grid, 2 AWG (Str.)
 to 250 kcmil, 5/8" Ground Rod
 Y
Other
 Penetrox E

Rated for Direct Burial
 UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Approvals / Certifications
 Y
 Y
 Y
 Compliant
 N
 N
 UL467, IEEE 837

Rod Size (Side B) - Range
 Copper Str Size (Side A) - Range

Conductor(s)
 5/8 in
 2 AWG-250 kcmil

Type of Plating
 Die Index (Side B)
 Die Index (Side A)
 Plated (Yes or No)
 Product Material

Physical
 Unplated
 1011
 997
 N
 Copper

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175