




BURNDY Catalog Number
UPC Number
Description
Status

YGLR34C34
 7818102208566
 250-500 GRD GRID TO 3/4
 Active



Web Use
 BURNDY Product Line



Length (in)
 B Length (in)
 D - in
 BB - Length (in)
 B Length (Fraction)

Dimensional

2.63
 0.75
 0.50
 0.88
 3/4

Product Description

General

Copper Compression Connector,
 Ground Rod to Grid, 250 kcmil -
 500 kcmil, 3/4" Ground Rod

Prefilled (Oxide Inhibitor)

Y

Type of Oxide Inhibitor

Other

Penetrox E

Approvals / Certifications

Rated for Direct Burial

Y

UL Listed

Y

CSA Certified

Y

ROHS Compatible

Compliant

UL Recognized

N

CULUS

N

Industry Standards

UL467, IEEE 837

Conductor(s)

Rod Size (Side B) - Range

3/4 in

Copper Str Size (Side A) - Range

250 kcmil-500 kcmil

Physical

Type of Plating

Unplated

Die Index (Side B)

1011

Die Index (Side A)

1011

Plated (Yes or No)

N

Product Material

Copper

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175