Pin Indication Type/Actuators/Limiters

MIS

Non-Time-Delay
Physical Size:
13/32″ × 2″
(10.3mm × 50.8mm)
Voltage Rating: 600Vac
Interrupting Rating: 200,000 AIC

Catalog Symbol & Current Ratings

600Vac		
MIS-1	MIS-4	MIS-10
MIS-2	MIS-5	MIS-12
MIS-3	MIS-8	

Test Specifications

Fuse	Load	Opening Time
All	110%	4 hrs. (min.)
1-5A	150%	6 min. (max.)
6-12A	150%	12 min. (max.)

KAZ

Actuator (Not a Fuse)
Physical Size:
13/32″ × 2″
(10.3mm × 50.8mm)
Voltage Rating: 600Vac
Interrupting Rating: 200,000A
Agency Information:
UL Listed, Guide JDVS, File E58836
Recommended Use: Mounts in Buss signal blocks 2778, 2837 and 2838.
General Information: Connects in parallel with fuses having a rating of 50 amperes or larger and opens at 10A or more.

CE logo denotes compliance with European Union Low Voltage Directive (50-1000Vac, 75-1500Vdc). Refer to Data Sheet: 8002 or contact Bussmann Application Engineering at 636-527-1270 for more information.

Data Sheet: 2021

ANN Limiter

Very Fast Acting
Physical Size:
7/8″ × 3 3/16″
(22.2mm × 81.0mm)
Voltage Rating: 125Vac IR = 2500A
80Vdc IR = 2700 A
Agency Information: 35-400A @ 125Vac, IR=2500A and 80Vdc, IR=2700A: UL Recognized Guide JFHR2, File E56412; CSA Certified Class 1422-30, File 53787
CE for 35-400A
Fuseholder: 4164

Catalog Symbol & Current Ratings

ANN-10	ANN-90	ANN-225	ANN-400
ANN-35	ANN-100	ANN-250	ANN-500
ANN-40	ANN-125	ANN-275	ANN-600
ANN-50	ANN-150	ANN-300	ANN-700
ANN-60	ANN-175	ANN-325	ANN-800
ANN-80	ANN-200	ANN-350	

Data Sheet: 2023 & 2133

ANL

Non-Time Delay
Voltage Rating: 80Vdc
Agency Information:
UL Recognized, CSA Certified, 35-750A @ 80Vdc, IR = 2700A Guide JFHR2, File E56412 Class 1422-30, File 53787
Fuseholder: 4164

Catalog Symbol & Current Ratings

ANL-35	ANL-125	ANL-250	ANL-500
ANL-40	ANL-130	ANL-275	ANL-600
ANL-50	ANL-150	ANL-300	ANL-675
ANL-60	ANL-175	ANL-325	ANL-750
ANL-80	ANL-200	ANL-350	—
ANL-100	ANL-225	ANL-400	—

Data Sheet: 2024 & 2133