



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## High Speed Fuse

170M4834

UPC:051712798518

### Dimensions:

- **Height:** 2.087 IN
- **Length:** 5.433 IN
- **Width:** .315 IN

**Weight:**1.6456 LB

### Warranties:

- Not Applicable

### Specifications:

- **Type:** Square body, 00TN/80 type T indicator for micro
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Amperage Rating:** 250A
- **Voltage Rating:** 700 Vac (UL), 690 Vac (IEC)
- **Interrupt Rating:** 150 kAIC
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Current Rating:** 250A RMS
- **Pre Arc (I<sup>2</sup>T):** 10000
- **Clearing (I<sup>2</sup>T):** Clearing at 1000V: 74000
- **Class:** Class aR
- **Connection:** Blade end X Din 43-620 blade end
- **Watt Losses:** 48W
- **Mounting:** Din 43 620 blade style

**Supporting documents:** No Data

### Certifications:

- IEC Rated
- UL Recognized

**Product compliance:**



- CE Marked
- RoHS Compliant

---

© 2016 Eaton. All rights reserved.