



Powering Business Worldwide

pe.eaton.com

Ferrule style high speed fuse links

FWP-25A14FI

UPC:051712510769

Dimensions:

- **Height:** 32 MM
- **Length:** 52 MM
- **Width:** 15 MM

Weight:.012 KG

Warranties:

- Not Applicable

Specifications:

- **Type:** FWP, Ferrule style
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Amperage Rating:** 25A
- **Voltage Rating:** 700 Vac, 600 Vdc (UL)
- **Interrupt Rating:** 200kA ac RMS Symmetrical, 50kA at 300 Vdc
- **Fuse Indicator:** With Indicator
- **Packaging Type:** Standard
- **Used With:** Finger safe holders/blocks and striker
- **Pre Arc (I²T):** 42
- **Clearing (I²T):** Clearing at Rated voltage: 234
- **Diameter:** 14 MM
- **Material:** Ceramic
- **Color:** White
- **Class:** aR
- **Connection:** Ferrule end X ferrule end
- **Watt Losses:** 4W
- **Mounting:** Fuse holder and blocks
- **Quantity:** 10
- **Fuse Size:** 14 x 51 mm



Supporting documents: No Data

Certifications:

- UL Recognized
- CSA Certified

Product compliance:

- CE Marked