



Powering Business Worldwide

pe.eaton.com

Ferrule style high speed fuse links

FWP-32A22F

UPC:051712796545

Dimensions:

- **Height:** 50 MM
- **Length:** 58 MM
- **Width:** 23 MM

Weight:.042 KG

Warranties:

- Not Applicable

Specifications:

- **Type:** FWP, Ferrule style
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Amperage Rating:** 32A
- **Voltage Rating:** 700 Vac (IEC), 700 Vdc (UL)
- **Interrupt Rating:** 200 KAIC, 50 KAIC at 300 Vdc
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Used With:** Finger safe holders/blocks and striker
- **Pre Arc (I2T):** 55
- **Clearing (I2T):** Clearing at Rated voltage: 780
- **Minimum Melting:** 53.5 I2t (A2 Sec)
- **Diameter:** 22 MM
- **Material:** Ceramic
- **Color:** White
- **Class:** Class aR
- **Connection:** Ferrule end X ferrule end
- **Watt Losses:** 8W
- **Mounting:** Fuse holder and blocks
- **Quantity:** 10



- **Fuse Size:** 22 x 58 mm

Supporting documents: No Data

Certifications:

- CSA Certified
- UL Recognized

Product compliance:

- CE Marked
- RoHS Compliant