



Powering Business Worldwide

pe.eaton.com

Ferrule style high speed fuse links

FWP-50A14F

UPC:051712370868

Dimensions:

- **Height:** 32 MM
- **Length:** 51 MM
- **Width:** 15 MM

Weight:.012 KG

Warranties:

- Not Applicable

Specifications:

- **Type:** FWP, Ferrule style
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Amperage Rating:** 50A
- **Voltage Rating:** 700 Vac (IEC), 800 Vdc Resistive (UL),
- **Interrupt Rating:** 200 KAIC, 50 KAIC at 300 Vdc
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Used With:** Finger safe holders/blocks and striker
- **Pre Arc (I²T):** 200
- **Clearing (I²T):** Clearing at Rated voltage: 1800
- **Minimum Melting:** 200 I²t (A² Sec)
- **Diameter:** 14 MM
- **Material:** Ceramic
- **Color:** White
- **Class:** Class aR
- **Connection:** Ferrule end X ferrule end
- **Watt Losses:** 9W
- **Mounting:** Fuse holder and blocks



- **Quantity:** 10
- **Fuse Size:** 14 x 51 mm

Supporting documents:

- [50AMP 700V AC FERRULE 14.3 X 50.8MM](#)

Certifications:

- UL Recognized
- CSA Certified

Product compliance:

- CE Marked
- RoHS Compliant