



Powering Business Worldwide

pe.eaton.com

Time-Delay Fuse

BK/MDA-12-R

UPC:051712657136

Dimensions:

- **Height:** 1.25 IN
- **Length:** .25 IN
- **Width:** .25 IN

Weight:.4 LB

Warranties: No Data

Specifications:

- **Type:** Electronic
- **Application:** Electronic circuits
- **Amperage Rating:** 12A
- **Voltage Rating:** 250 Vac, 32 Vdc (self certified)
- **Interrupt Rating:** 750 AIC at 250 Vac, 10 kAIC at 125 Vac
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Response Time:** 60 min. maximum at 135%, 120 secs. maximum at 200%
- **Voltage Drop:** Typical: .128 mV
- **Melting (L2T):** Typical: 125.18
- **Diameter:** .25 IN
- **Material:** Ceramic tube, nickel-plated brass endcaps
- **Connection:** Ferrule end X ferrule end
- **Quantity:** 100
- **Resistance:** Typical DC cold: .00755 ohms

Supporting documents:

- [5X20MM FUSE HOLDER](#)

Certifications: No Data

Product compliance:

- CE Marked
- RoHS Compliant



