

### TYPE GRM GRF

#### Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Type GRM - Elongated steel stud
- Type GRF - Threaded female design

#### Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of grounding a single conductor to steel structures or to tap a single conductor from bus bar
- Provides ease of installation for a variety of standard stud sizes




Fig. 1




Fig. 2

Catalog Number	Figure Number	Wire Range Single Cable				Dia. Thread	Dimensions			Hex Size
		Max.	Min.	Steel Strand	A		B	L		
GRM-2A	1	2str	12sol/str	5/16	1/4"-20	-	11/16	1-1/4	Slot	
GRM-2B	1	2str	12sol/str	5/16	5/16"-18	-	3/8	1-1/4	Slot	
GRM-2C	1	2str	12sol/str	5/16	3/8"-16	-	9/16	1-1/4	Slot	
GRM-0	1	1/0str	2str	3/8	1/2"-13	-	1	1-9/16	Slot	
GRM-250A	1	250kcmil	1/0	9/16	1/2"-13	-	1	2-1/8	5/16	
GRM-250B	1	250kcmil	1/0	9/16	5/8"-11	-	1	2-1/8	5/16	
GRM-350	1	350kcmil	4/0	-	5/8"-11	-	1	2-1/2	3/8	
GRM-500	1	500kcmil	350kcmil	-	3/4"-10	-	1-3/8	2-15/16	3/8	
GRM-750	1	750kcmil	500kcmil	-	3/4"-10	-	1-3/8	3-3/8	1/2	
GRF-2A	2	2str	12sol/str	5/16	1/4"-20	5/16	-	1-1/4	Slot	
GRF-2B	2	2str	12sol/str	5/16	5/16"-18	3/8	-	1-1/4	Slot	
GRF-2C	2	2str	12sol/str	5/16	3/8"-16	7/16	-	1-1/4	Slot	
GRF-0	2	1/0str	2str	3/8	1/2"-13	1/2	-	1-9/16	Slot	
GRF-250A	2	250kcmil	1/0	9/16	1/2"-13	1/2	-	2-1/8	5/16	
GRF-250B	2	250kcmil	1/0	9/16	5/8"-11	3/4	-	2-1/8	5/16	
GRF-350	2	350kcmil	4/0	-	5/8"-11	3/4	-	2-1/2	3/8	
GRF-500	2	500kcmil	350kcmil	-	3/4"-10	7/8	-	2-15/16	3/8	
GRF-750	2	750kcmil	500kcmil	-	3/4"-10	7/8	-	3-3/8	1/2	

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)  
DE-OX Inhibitor is recommended for all aluminum terminations.

### TYPE GRM GRF

#### Features

- Manufactured from high strength 6061-T6 aluminum alloy
- Electro-tin plated
- Type GRM - Elongated steel stud
- Type GRF - Threaded female design

#### Benefits

- Suitable for use with either copper or aluminum conductors
- Provides low contact resistance
- Provides ease of grounding a single conductor to steel structures or to tap a single conductor from bus bar
- Provides ease of installation for a variety of standard stud sizes




Fig. 1




Fig. 2

Catalog Number	Figure Number	Wire Range Single Cable				Dimensions			Hex Size
		Max.	Min.	Steel Strand	Dia. Thread	A	B	L	
GRM-2A	1	2str	12sol/str	5/16	1/4"-20	-	11/16	1-1/4	Slot
GRM-2B	1	2str	12sol/str	5/16	5/16"-18	-	3/8	1-1/4	Slot
GRM-2C	1	2str	12sol/str	5/16	3/8"-16	-	9/16	1-1/4	Slot
GRM-0	1	1/0str	2str	3/8	1/2"-13	-	1	1-9/16	Slot
GRM-250A	1	250kcmil	1/0	9/16	1/2"-13	-	1	2-1/8	5/16
GRM-250B	1	250kcmil	1/0	9/16	5/8"-11	-	1	2-1/8	5/16
GRM-350	1	350kcmil	4/0	-	5/8"-11	-	1	2-1/2	3/8
GRM-500	1	500kcmil	350kcmil	-	3/4"-10	-	1-3/8	2-15/16	3/8
GRM-750	1	750kcmil	500kcmil	-	3/4"-10	-	1-3/8	3-3/8	1/2
GRF-2A	2	2str	12sol/str	5/16	1/4"-20	5/16	-	1-1/4	Slot
GRF-2B	2	2str	12sol/str	5/16	5/16"-18	3/8	-	1-1/4	Slot
GRF-2C	2	2str	12sol/str	5/16	3/8"-16	7/16	-	1-1/4	Slot
GRF-0	2	1/0str	2str	3/8	1/2"-13	1/2	-	1-9/16	Slot
GRF-250A	2	250kcmil	1/0	9/16	1/2"-13	1/2	-	2-1/8	5/16
GRF-250B	2	250kcmil	1/0	9/16	5/8"-11	3/4	-	2-1/8	5/16
GRF-350	2	350kcmil	4/0	-	5/8"-11	3/4	-	2-1/2	3/8
GRF-500	2	500kcmil	350kcmil	-	3/4"-10	7/8	-	2-15/16	3/8
GRF-750	2	750kcmil	500kcmil	-	3/4"-10	7/8	-	3-3/8	1/2

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)  
DE-OX Inhibitor is recommended for all aluminum terminations.