**Product Number:** 72994

**Order Abbreviation:** WALPAK1C/055347750/CO/BZ

**General Description:** Walpack Cutoff 1C, 55 Watts, 347V, 70+ CRI, 5000K, cutoff distribution, bronze finish

## Product Information

| | |
|---|---|
| Power Factor | ?0.90 |
| Primary Lamp Type | COB |
| Minimum Operating Temperature - Celsius | -40 |
| Minimum Operating Temp - Fahrenheit | -40 |
| Primary Lamp Type 1 | COB |
| Total Harmonic Distortion (THD) | ?20 % |
| Efficacy (LPW) | 55 |
| Abbrev. With Packaging Info. | WALPAK1C055347750COBZ 1/CS 1/SKU |
| Color Temperature/CCT (K) | 5000 |
| Ordering Abbreviation | WALPAK1C/055347750/CO/BZ |
| Average Rated Life 1 (hr) | 150000 |
| Lumens | 5500 |
| Nominal Voltage (V) | 347.00 |
| Nominal Wattage (W) | 55.00 |
| UPC Code | UPC046135729942 |
| Color Rendering Index (CRI) | >70 |
| Service Life Rating | ?150000 |
| Lumens (lm) | 5500 |
| Wattage (W) | 55.00 |
| Color Range | 5000 K |
| Connectors | Flying leads |
| Energy Star Rated | No |
| Fixture Warranty | 5 years |
| Housing | Aluminum |
| Luminaire Finish | Bronze |
| Luminaire Type | Wall pack |
| Maximum Operating Temperature-Celsius | 40 |
| Maximum Operating Temperature-Fahrenheit | 104 |
| Power Input | 55 |
| Mounting | Surface |
| Dimensions | 14.4x11.42x9.45 |
| Certification Listing | cULus, FCC, RoHS, DLC |