



# Core & Coil (71A) MH ~GT~ 450W

## CORE & COIL HID MH BAL 1000W M141 QUAD KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information				
ANSI Code	M141			
Lamp Type	1000W MH			
Number of Lamps	1 piece/unit			
Circuit Type	SUPER-CWA			
Ballast Type	Magnetic HID			
Base Model	71A6593			
Core Size	4 1/4 x 6 (2 Coil)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI571-H5			
Ignitor Temperature Rating	105°C			
Capacitor Value	24 MFD			
Capacitor Catalog Number	MD2409000			
Capacitor Requirements	480V			
Capacitor Temperature Rating	90°C			
Capacitor Diameter/Oval Dimensions	1.75 in			
Capacitor Height	3.9 in			
Automatic Restart	No			

Operating and Electrical	
Input Voltage	120/208/240/277 V
Input Frequency	60 Hz
Power (Rated) (Nom)	1000 W
Inp. Current (Open Circuit)	4.5/2.7/2.3/2.2 A
Input Current (Starting)	7.8/4/3.7/3.2 A
Input Current (Short Circuit)	5.6-8.6/3.2-4.8/2.8-4.3/2.4-3.75 V
Secondary Short Circuit Current	5.2-6.4 A
Constant Wattage Deviation	12%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	430 V
Input Current (Operating) (Nom)	9/5.2/4.5/3.9 A A
Input Power (Nom)	1080 W
Rated Lamp Watts	1000W W
Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded


Datasheet, 2015, December 22 data subject to change

# Core & Coil (71A) MH ~GT~ 450W

Remote Wiring Configuration Allowed	Yes				
Max Ballast-Lamp Distance Remote Wiring	5'				
Recommended Fuse Value	20/15/10/10 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	385-475 V				
Approbation Marks	ULR RoHS Compliant				
Temperature Marking	D/B/B/B				
UL Recognized	Yes				
Hipot Test (1 Minute)	1500 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029D				

Product Data			
Order product name	CORE & COIL HID 71A659300		
EAN/UPC - Product	781087062401		
Order code	71A6593001		
ocal order code	505149		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	1		
Material Nr. (12NC)	913710651101		
Net Weight (Piece)	10.469 kg		

## **Dimensional drawing**



MH BAL 1000W M141 QUAD KIT

Product	C1	C2	A1	A2	A3	B1	B2
CORE & COIL HID 71A6593001	4.5 in	2.8 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in

