



# Core & Coil (71A) MH 175W - 450W

## CORE & COIL HID MH BAL 320W M132/154 QUAD KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information				
ANSI Code	M132-M154			
Lamp Type	320W MH			
Number of Lamps	1 piece/unit			
Circuit Type	SUPER-CWA			
Ballast Type	Magnetic HID			
Base Model	71A5892A			
Core Size	4 1/4 x 4 3/4 (2 coil)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI533-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	21 MFD			
Capacitor Catalog Number	7C210P34R			
Capacitor Requirements	345V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.75 in			
Capacitor Height	4.8 in			
Automatic Restart	No			

Operating and Electrical	
Input Voltage	120/208/240/277 V
Input Frequency	60 Hz
Power (Rated) (Nom)	320 W
Inp. Current (Open Circuit)	2.3/1.35/1.15/1 A
Input Current (Starting)	1.8/1.05/0.9/0.8 A
Input Current (Short Circuit)	1.65-2.5/1-1.5/0.8-1.25/0.7-1.1 A
Secondary Short Circuit Current	2.9-3.6 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	270 V
Input Current (Operating) (Nom)	3.25/1.9/1.65/1.4 A A
Input Power (Nom)	368 W
Rated Lamp Watts	320W W
Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"


Datasheet, 2015, November 29 data subject to change

### Core & Coil (71A) MH 175W - 450W

Wire Type	Stranded Yes 2'				
Remote Wiring Configuration Allowed					
Max Ballast-Lamp Distance Remote Wiring					
Recommended Fuse Value	8/6/5/3 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	250-300 V				
Approbation Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	B/B/B/B				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				

UL Temperature Code	1029B				
Product Data					
Order product name	CORE & COIL HID 71A5892001D				
EAN/UPC - Product	781087096178				
Order code	71A5892001D				
Local order code	192393				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	1				
Material Nr. (12NC)	913700535309				
Net Weight (Piece)	5.149 kg				

#### **Dimensional drawing**



MH BAL 320W M132/154 QUAD KIT

Product	C1	C2	<b>A</b> 1	A2	B1	B2
CORE & COIL HID 71A5892001D	3.65 in	1.8 in	4.8 in	4.4 in	4.3 in	3.9 in

