**PHILIPS** Lighting



# Core & Coil (71A) HPS ~LT~ 200W

## CORE & COIL HID HPS BAL 150W S55 120V C&C

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information		
ANSI Code	S55	
Lamp Type	150W HPS	
Number of Lamps	1 piece/unit	
Circuit Type	R-HPF	
Ballast Type	Magnetic HID	
Base Model	71A8107	
Core Size	2 5/8 x 2 3/16	
Suitable For Outdoor Use	Yes	
Ignitor Catalog Number	LI551-H4	
Ignitor Temperature Rating	105°C	
Capacitor Value	55 MFD	
Capacitor Catalog Number	7C550P12RA	
Capacitor Requirements	120V	
Capacitor Temperature Rating	105°C	
Capacitor Diameter/Oval Dimensions	1.75 in	
Capacitor Height	3.75 in	
Automatic Restart	No	


Operating and Electrical	
Input Voltage	120 V
Input Frequency	60 Hz
Power (Rated) (Nom)	150 W
Inp. Current (Open Circuit)	2.35 A
Input Current (Starting)	2.25 A
Input Current (Short Circuit)	1.65-2.75 A
Secondary Short Circuit Current	3.65-5.55 A
Constant Wattage Deviation	Within Trapezoid
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	120 V
Input Current (Operating) (Nom)	1.5 A A
Input Power (Nom)	170 W
Rated Lamp Watts	150W W
Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded

### Core & Coil (71A) HPS ~LT~ 200W


Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	2'
Recommended Fuse Value	8 A
Approval and Application	
Open Circuit Voltage Test (Volts)	114-126 V
Approbation Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	A
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)

UL Temperature Code	1029A
Product Data	
Order product name	CORE & COIL HID 71A8107500D
EAN/UPC - Product	781087810750
Order code	71A8107500D
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913700526309
Net Weight (Piece)	1.665 kg

#### **Dimensional drawing**



HPS BAL 150W S55 120V C&C





© 2016 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2016, February 1 - data subject to change