



Core & Coil (71A) LPS

CORE & COIL HID LPS BAL 35/55W L70/71 QUAD KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information				
ANSI Code	L71			
Lamp Type	55W LPS			
Number of Lamps	1 piece/unit			
Circuit Type	HX-HPF			
Ballast Type	Magnetic HID			
Base Model	71A0490			
Core Size	3 X 4 (2 coil)			
Suitable For Outdoor Use	Yes			
Capacitor Value	14 MFD			
Capacitor Catalog Number	7C140M30RA			
Capacitor Requirements	240V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.65 in			
Capacitor Height	2.75 in			
Automatic Restart	No			
Operating and Electrical				
Input Voltage	120/208/240/277 V			
Input Frequency	60 Hz			
Power (Rated) (Nom)	55 W			
Inp. Current (Open Circuit)	2.35/1.39/1.18/0.98 A			
Input Current (Starting)	0.8/0.46/0.39/0.36 A			
	·			

Input Current (Short Circuit)	0.36-0.54/0.23-0.34/0.2-0.3/0.16-0.25 A				
Secondary Short Circuit Current	0.5-0.7 A				
Constant Wattage Deviation	10%				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Nominal Open Circuit Voltage	480 V				
Input Current (Operating) (Nom)	0.73/0.42/0.36/0.32 A A				
Input Power (Nom)	80 W				
Rated Lamp Watts	55W W				
Wiring					
Wire Striplength	0.5 mm				
Wire Length By Color	12"				
Wire Type	Stranded				
Remote Wiring Configuration Allowed	Yes				
Max Ballast-Lamp Distance Remote Wiring	Determined by AWG used				
Recommended Fuse Value	6/4/3/3 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	430-530 V				
Approbation Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	A/A/A/A				
UL Recognized	Yes				


Datasheet, 2016, February 1 data subject to change

Core & Coil (71A) LPS

Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029A				
Product Data					
Order product name	CORE & COIL HID 71A0490001D				
EAN/UPC - Product	781087025567				

Order code	71A0490001D			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	1			
Material Nr. (12NC)	913700502031			
Net Weight (Piece)	3.362 kg			

Dimensional drawing



Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A0490001D	3.5 in	2.25 in	3.9 in	3.5 in	2.8 in	2.4 in

