



Core & Coil (71A) MH ~GT~ 450W

CORE & COIL HID MH BAL 1500W M48 QUAD KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information					
ANSI Code	M48				
Lamp Type	1500W MH				
Number of Lamps	1 piece/unit				
Circuit Type	CWA				
Ballast Type	Magnetic HID				
Base Model	71A6772				
Core Size	4 1/4 x 6 (2 Coil NB)				
Suitable For Outdoor Use	Yes				
Ignitor Catalog Number	NA				
Ignitor Temperature Rating	NA				
Capacitor Value	32 MFD				
Capacitor Catalog Number	MD3202100				
Capacitor Requirements	525V				
Capacitor Temperature Rating	90°C				
Capacitor Diameter/Oval Dimensions	2 in				
Capacitor Height	3.75 in				
Automatic Restart	No				

Operating and Electrical					
Input Voltage	120/208/240/277 V				
Input Frequency	60 Hz				
Inp. Current (Open Circuit)	5.72/3.29/3.04/2.57 A				
Input Current (Starting)	10.8/6.13/5.42/4.72 A				
Input Current (Short Circuit)	9.1-13.6/5.22-7.83/4.56-6.84/3.96-5.95 V				
Secondary Short Circuit Current	7.29-8.9 A				
Constant Wattage Deviation	12%				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Nominal Open Circuit Voltage	460 V				
Input Current (Operating) (Nom)	13.4/7.8/6.8/5.9 A A				
Input Power (Nom)	1610 W				
Rated Lamp Watts	1500 W				
Wiring					
Wire Striplength	0.5 mm				
Wire Length By Color	12"				
Wire Type	Stranded				
Remote Wiring Configuration Allowed	Yes				


Datasheet, 2016, February 1 data subject to change

Core & Coil (71A) MH ~GT~ 450W

Max Ballast-Lamp Distance Remote Wiring	Determined by AWG used 30/25/20/15 A			
Recommended Fuse Value				
Approval and Application				
Open Circuit Voltage Test (Volts)	414-506 V			
Approbation Marks	ULR CSA certificate RoHS Compliant			
Temperature Marking	G/E/E/G			
UL Recognized	Yes			
Hipot Test (1 Minute)	2000 V			
Hipot Test (2 Seconds)	2500 V			
UL Insulation Class	H(180°C)			
UL Temperature Code	1029G			

Product Data	
Order product name	CORE & COIL HID 71A677200
EAN/UPC - Product	781087677216
Order code	71A6772001
lumerator - Quantity Per Pack	1
lumerator - Packs per outer box	1
/laterial Nr. (12NC)	913700574909
Net Weight (Piece)	14.370 kg

Dimensional drawing



MH BAL 1500W M48 QUAD KIT

Product	C1	C2	A1	A2	A3	B1	B2
CORE & COIL HID 71A6772001	6.7 in	4.7 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in

