



Standard

STANDARD MAG BALLAST (2) 26W COMPACT(2-PIN) 120V

Available for many fluorescent lamp types sold today, including Preheat, Rapid Start, 2-pin CFL, Slimline, High Output, Very High Output and Circline. Magnetic ballasts can be used in any application where these lamps are used.

Product data

General Information	
Lamp Type	CFQ26W/G24D
Number of Lamps	2 piece/unit
Lamp Footage	-
Ballast Type	Magnetic Fluorescent
Base Model	H2Q26TPBLS
Suitable For Outdoor Use	Yes
Automatic Restart	Yes
Operating and Electrical	
Input Voltage	120 V
Input Frequency	60 Hz
Max THD	15 %
Power (Rated) (Nom)	26 W
Starting Method	Preheat
Lamp Current Crest Factor (Nom)	1.7
Ignition Time (Nom)	1 s
Inp. Current (Open Circuit)	0
Ballast Factor (Nom)	0.9
Power Factor (Nom)	0.98
Input Current (Operating) (Nom)	0.44 A

Input Power (Nom)	52 W
Rated Lamp Watts	26W W
Wiring	
Wire Striplength	0.50/0.375 mm
Lamp Connection	Series
Wire Length By Color	See data sheet
Wire Gauge (Nom)	18AWG mm
Wire Type	Solid
Remote Wiring Configuration Allowed	Yes
Tandem Wiring Configuration Allowed	Yes
Through Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	30'
Max Ballast-Lamp Distance Tandem Wiring	Any = 30'
Max Ballast-Lamp Distance Through Wiring	Any = 30'
Mechanical and Housing	
Housing Material	Metal
Housing	R5
Housing Dimensions	9.5" x 2.38" x 1.69"

Standard

Approval and Application


EMC Immunity Standard	FCC Non-Consumer
Sound Rating	A
UL Recognized	No

Product Data

Order product name	STANDARD H2Q26TPBLSM
EAN/UPC - Product	781087002254

Order code	H2Q26TPBLSM
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	913700589709
Net Weight (Piece)	1.611 kg

Dimensional drawing



MAG BALLAST (2) 26W COMPACT(2-PIN) 120V

Product	A1	A2	B1	C1
STANDARD H2Q26TPBLSM	9.5 in	8.91 in	2.38 in	1.69 in

