



Core & Coil (71A) MH 175W - 450W

CORE & COIL HID MH BAL 400W M135/M155 5-TAP KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information				
ANSI Code	M135-M155			
Lamp Type	400W MH			
Number of Lamps	1 piece/unit			
Circuit Type	SUPER-CWA			
Ballast Type	Magnetic HID			
Base Model	71A6052A			
Core Size	4 1/4 x 4 3/4 (2 coil)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI533-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	26 MFD			
Capacitor Catalog Number	7C260P33R			
Capacitor Requirements	330V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.75 in			
Capacitor Height	4.8 in			
Automatic Restart	No			

Operating and Electrical					
Input Voltage	120/208/240/277/480 V				
Input Frequency	60 Hz				
Power (Rated) (Nom)	400 W				
Inp. Current (Open Circuit)	2.7/1.6/1.3/0.8/0.65 A				
Input Current (Starting)	3/1.7/1.5/1.2/0.75 A				
Input Current (Short Circuit)	2.2-3.4/1.35-2.1/1.1-1.7/0.75-1.3/0.55-0.85 A				
Secondary Short Circuit Current	3.6-4.4 A				
Constant Wattage Deviation	10%				
Ballast Factor (Nom)	1				
Power Factor (Nom)	0.90				
Nominal Open Circuit Voltage	275 V				
Input Current (Operating) (Nom)	3.8/2.3/1.9/1.65/0.95 A A				
Input Power (Nom)	454 W				
Rated Lamp Watts	400W W				
Wiring					
Wire Striplength	0.5 mm				
Wire Length By Color	12"				


Datasheet, 2017, February 2 data subject to change

Core & Coil (71A) MH 175W - 450W

Wire Type	Stranded				
Remote Wiring Configuration Allowed	Yes				
Max Ballast-Lamp Distance Remote Wiring	2'				
Recommended Fuse Value	10/7/5/5/3 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	250-305 V				
Approbation Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	B/D/D/B/D				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				

1029D		
CORE & COIL HID 71A6052001D		
781087087695		
71A6052001D		
1		
1		
913701115001		
7.244 kg		

Dimensional drawing



MH BAL 400W M135 OR M155 5-TAP KIT

Product	C1	C2	A 1	A2	B1	B2
CORE & COIL HID 71A6052001D	4.3 in	2.2 in	4.8 in	4.4 in	4.3 in	3.9 in

