



# Core & Coil (71A) HPS ~LT~ 200W

## CORE & COIL HID HPS BAL 50W S68 QUAD KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information				
ANSI Code	S68			
Lamp Type	50W HPS			
Number of Lamps	1 piece/unit			
Circuit Type	HX-HPF			
Ballast Type	Magnetic HID			
Base Model	71A7891			
Core Size	3 X 4 (2 coil)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI551-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	5 MFD			
Capacitor Catalog Number	7C050L30RA			
Capacitor Requirements	300V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.25 in			
Capacitor Height	2.25 in			
Automatic Restart	No			

Operating and Electrical	
Input Voltage	120/208/240/277 V
Input Frequency	60 Hz
Power (Rated) (Nom)	50 W
Inp. Current (Open Circuit)	1/0.57/0.5/0.45 A
Input Current (Starting)	0.65/0.37/0.32/0.3 A
Input Current (Short Circuit)	0.6-0.8/0.32-0.48/0.3-0.4/0.25-0.35 A
Secondary Short Circuit Current	1.3-1.9 A
Constant Wattage Deviation	Within Trapezoid
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Nominal Open Circuit Voltage	125 V
Input Current (Operating) (Nom)	0.61/0.35/0.31/0.26 A A
Input Power (Nom)	66 W
Rated Lamp Watts	50W W
Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded


Datasheet, 2015, November 29 data subject to change

# Core & Coil (71A) HPS ~LT~ 200W

Remote Wiring Configuration Allowed	Yes			
Max Ballast-Lamp Distance Remote Wiring	2'			
Recommended Fuse Value	3/2/2/1 A			
Approval and Application				
Open Circuit Voltage Test (Volts)	115-135 V			
Approbation Marks	ULR CSA certificate RoHS Compliant			
Temperature Marking	A/A/A/A			
UL Recognized	Yes			
Hipot Test (1 Minute)	2000 V			
Hipot Test (2 Seconds)	2500 V			
UL Insulation Class	H(180°C)			
UL Temperature Code	1029A			

Product Data			
Order product name	CORE & COIL HID 71A7891001D		
EAN/UPC - Product	781087087985		
Order code	71A7891001D		
Local order code	500769		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	1		
Material Nr. (12NC)	913701115201		
Net Weight (Piece)	1.937 kg		

## **Dimensional drawing**



HPS BAL 50W S68 QUAD KIT

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A7891001D	2.2 in	1 in	3.9 in	3.5 in	2.8 in	2.4 in

