

SITOR fuse link, with blade contacts, NH3, In: 850 A, gR, Un AC: 690 V, Front indicator



Figure similar

Model	
product brandname	SETRON
Product designation	SITOR fuse link
Design of the product	With blade contacts
Design of an identification indicator	front indicator
Design of the switching contact	With blade contacts, silver-plated
Design of the fuse link	SITOR, LV HRC design
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH3
Operating class of the fuse link	gR
circuit-breaker / Design	3NE
Varying load factor (WL)	1
Switching capacity	
Switching capacity current	100 kA
• acc. to IEC 60947-2 / rated value	
Dissipation	

Power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	76 W
• maximum	76 W

Electricity	
rated current I _n / IEC, DIN/VDE / at 40 Cel	850 A
Current / at AC / rated value	850 A

Product details	
Product description	Not non-interchangeable

Mechanical Design	
Mounting position	Any, preferably vertical

Environmental conditions	
Ambient temperature	
• minimum	-20 °C
• maximum	50 °C
Environmental category	-20 to +50 at 95% relative humidity

Certificates	
Equipment marking	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval	Declaration of Conformity	other
---------------------------------	----------------------------------	--------------



[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE1448-2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NE1448-2/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE1448-2

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

