

SENTRON, Fuse switch disconnecter 3NP5, 3-pole, NH00, 160 A, for assembly and installation on mounting plate, with High-speed closing, screw terminal, Auxiliary switch on switch disconnecter: 1 NO+1 NC



Figure similar

Model	
Product brand name	SENTRON
Product designation	3NP5 fuse switch disconnecter
Design of the product	auxiliary switch at the switch disconnecter: 1 NO + 1 NC
Design type	For assembly and installation with auxiliary switch 1 NO+1 NC, with high-speed closing
Design of the operating mechanism	Cover handle
Design of the load switch / Strip form	No

General technical data	
Number of poles	3
Size of disconnecting link	NH000, NH00
Size of fuse link	NH000, NH00
Continuous current / at 35 °C / rated value	160 A
power factor cos phi / in utilization category	
• AC-21 B / at 400 V	0.95
• AC-21 B / at 500 V	0.95
• AC-22 B / at 400 V	0.65

• AC-22 B / at 500 V	0.65
circuit-breaker / Design	3NP506
Mounting type	Fixed mounting
Fuse system	LV HRC fuse

### Voltage

Type of voltage	AC/DC
Insulation voltage / rated value	690 V
Surge voltage resistance / rated value	6 kV

### Protection class

Protection class IP / on the front	IP00
------------------------------------	------

### Dissipation

Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	2.66 W
---	--------

### Electricity

Current / rated value	160 A
Continuous current	
• rated value	160 A
• at 40 °C / rated value	160 A
• at 45 °C / rated value	160 A
• at 50 °C / rated value	157 A
• at 55 °C / rated value	152 A
• at 60 °C / rated value	144 A
• at 65 °C / rated value	136 A
• at 70 °C / rated value	128 A
Let-through current / I <sub>2</sub> t / maximum permissible / in utilization category	
• AC-21 B / at 400 V	225 000 A <sup>2</sup> ·s
• AC-21 B / at 500 V	225 000 A <sup>2</sup> ·s
• AC-22 B / at 400 V	225 000 A <sup>2</sup> ·s
• AC-22 B / at 500 V	225 000 A <sup>2</sup> ·s
Let-through current / I <sub>c</sub> / maximum permissible / in utilization category	
• AC-21 B / at 400 V	15 kA
• AC-21 B / at 500 V	15 kA
• AC-22 B / at 400 V	15 kA
• AC-22 B / at 500 V	15 kA

### Main circuit

Operating voltage	
• at AC / at 50/60 Hz / rated value	690 V
• at AC / rated value / maximum	690 V
• at DC / rated value	440 V

Rated current I <sub>e</sub> / maximum / in utilization category	
• AC-21 B / at 400 V	160 A
• AC-21 B / at 500 V	160 A
• AC-22 B / at 400 V	160 A
• AC-22 B / at 500 V	160 A

### Suitability

Suitability for use	system protection
• Main switch	No
• switch disconnecter	Yes
• EMERGENCY OFF switch	No
• safety switch	Yes

### Product function

Product function / fuse monitoring	No
------------------------------------	----

### Short circuit

Maximum short-circuit current breaking capacity (I <sub>cu</sub> ) / at 400 V / rated value	1.6 kA
Conditional rated short-circuit current / in utilization category	
• AC-21 B / at 400 V	50 kA
• AC-21 B / at 500 V	50 kA
• AC-22 B / at 400 V	50 kA
• AC-22 B / at 500 V	50 kA

### Connections

Type of electrical connection	2.5 - 150 mm <sup>2</sup> DIN 46 234 a. up to 95 mm <sup>2</sup> DIN 46 235
• for main current circuit	screw-type terminals

### Mechanical Design

Height	196 mm
Width	134 mm
Depth	97.5 mm
Number of width units	1
Mounting type	Mounting plate
Mounting type	
• floor mounting	Yes
• front mounting	No
• rail mounting	No
Net weight	1 639 g

### Environmental conditions

Degree of pollution	3
Installation altitude / at height above sea level / maximum	2 000 m

Ambient temperature	
• during operation / minimum	-25 °C
• during operation / maximum	55 °C
• during storage / minimum	-50 °C
• during storage / maximum	80 °C

## Certificates

Reference code	
• acc. to DIN EN 61346-2	Q
• acc. to DIN EN 81346-2	Q

General Product Approval	Declaration of Conformity	Test Certificates	other
--------------------------	---------------------------	-------------------	-------



CCC

[Miscellaneous](#)



EG-Konf.

[Special Test Certificate](#)

[Confirmation](#)

[Miscellaneous](#)

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NP5060-0CA10>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3NP5060-0CA10>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NP5060-0CA10](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NP5060-0CA10)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>



