

TRANSVERSE AUXILIARY SWITCH WITH SCREW CONNECTION, 2NO



Figure similar

General technical data:

product brand name		SIRIUS
Product designation		auxiliary switch, transverse on the front
Size of the circuit-breaker		S00, S0, S2, S3
Protection class IP on the front		IP20
Ambient temperature		
• during storage	°C	-50 ... +80
• during operation	°C	-20 ... +60

Auxiliary circuit:

Number of NC contacts for auxiliary contacts instantaneous contact		0
Number of NO contacts for auxiliary contacts instantaneous contact		2
Number of CO contacts of auxiliary contacts instantaneous contact		0
Operating current		
• of auxiliary contacts		
— at AC-12		
— at 24 V	A	2.5

- at 230 V
- maximum
- at AC-15
- at 24 V
- at 230 V
- at DC-13
- at 24 V
- at 48 V
- at 60 V

A	2.5
A	10
A	2
A	0.5
A	1
A	0.3
A	0.15

Installation/ mounting/ dimensions:






Mounting type		plug-in fixing
Width	mm	45
Height	mm	12
Depth	mm	17

Connections/ Terminals:

Type of electrical connection for auxiliary and control current circuit		screw-type terminals
Type of connectable conductor cross-sections		
• for auxiliary contacts		
— solid		2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²)
— finely stranded		
— with core end processing		2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²)
• at AWG conductors for auxiliary contacts		2x (18 ... 14)

Certificates/ approvals:

Certificate of suitability	CE / UL / CSA / CCC
-----------------------------------	---------------------

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
 CCC	 CSA	 UL	 EG-Konf.
		spezielle Prüfbescheinigungen n	 BUREAU VERITAS

Shipping Approval	other
--------------------------	--------------


[Umweltbestätigung](#)
[Bestätigungen](#)


Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3RV19011F>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RV19011F>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3RV19011F&lang=en

last modified:

29.02.2016