


ENCLOSURE FOR COMMAND DEVICES, 22MM, ROUND,
ENCLOSURE MATERIAL PLASTIC, ENCLOSURE TOP PART
GRAY, 1 COMMAND POINT, UNEQUIPPED, FLOOR MOUNTING,
1 X M20 EACH AT TOP AND BOTTOM



Enclosure:

Design of the housing	Empty enclosure for command and signaling devices
Shape of the enclosure front	Square
Material of the enclosure	plastic
Number of command points	1
Product component • protective collar	No
Color • of top part of the enclosure	grey
Delivery state • as a kit • pre-wired on strip terminal	No No
Mounting type of the enclosure	Vertical / horizontal

Actuator:

Product feature • lockout	No
Product extension optional Light source	Yes

Front ring:

Product component front ring	No
-------------------------------------	----

General technical data:

Product function • positive opening • EMERGENCY STOP function	No No
Product component • Light source • Stand/pedestal	No No
Protection class IP	IP65
Vibration resistance • acc. to IEC 60068-2-6	20 ... 200 Hz: 5g
Equipment marking • acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 • acc. to DIN EN 61346-2 • acc. to DIN EN 81346-2	S U U

Connections/ Terminals:

Type of electrical connection on enclosure	Cable routing above, below / left, right, each 1 x M20
---	--

Ambient conditions:

Ambient temperature • during operation • during storage	-25 ... +70 °C -40 ... +80 °C
--	----------------------------------

Environmental category during operation acc. to IEC 60721	3K6
---	-----

Installation/ mounting/ dimensions:

Mounting type	
• of contact blocks, socket, and accessories	Floor mounting / front mounting (1-pole)
Height	85 mm
Width	85 mm
Depth	64 mm
Shape of the installation opening	round
Mounting diameter	22 mm

Accessories:

Number of labels	1
Product component holder for 3 switching elements	No

Certificates/approvals

General Product Approval		Declaration of Conformity	Test Certificates	Shipping Approval	
 CSA	 UL		 EG-Konf.	spezielle Prüfbescheinigungen <u>n</u>	 ABS

Shipping Approval			other	
 DNV	 LRS	 PRS	Umweltbestätigung	Bestätigungen

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB38010AA3>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB38010AA3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB38010AA3>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB38010AA3&lang=en



last modified:

WS 444;
WS 25; 3SB3801-0AA3_ALL
21.03.2016