

COMPONENT FOR AS-I ENCLOSURE METAL ENCLOSURE
WITHOUT PROTECTIVE COLLAR AS-I F-SLAVE 2 SAFE INPUTS
FOR 1-6 COMMAND POSITIONS



Figure similar

Product designation	F-slave
General technical data:	
Protection class IP	IP20
Equipment marking	
<ul style="list-style-type: none"> • acc. to DIN EN 61346-2 • acc. to DIN EN 81346-2 	<p>K</p> <p>K</p>
Safety related data:	
Safety Integrity Level (SIL) acc. to IEC 61508	SIL3
Ambient conditions:	
Ambient temperature	
<ul style="list-style-type: none"> • during operation 	-25 ... +70 °C
Inputs/ Outputs:	
Number of digital inputs	2
<ul style="list-style-type: none"> • safety-related 	2
Number of digital outputs	0
Installation/ mounting/ dimensions:	
Mounting type	floor mounting
Height	71 mm
Width	17.6 mm
Depth	50.1 mm
Certificates/ approvals:	

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity	Shipping Approval
--------------------------	---------------------------------------	---------------------------	-------------------



[Type Examination Certificate](#)



Shipping Approval	other
-------------------	-------



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3SF5500CA>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SF5500CA>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3SF5500CA&lang=en

last modified:

02.06.2015