

OUTPUT INTERFACE !!! PHASE-OUT PRODUCT !!! FOR
FURTHER INFORMATION PLEASE CONTACT OUR SALES
STAFF! 1C/O, SCREW TERMINAL 24 V AC/DC HOUSING WIDTH
6.2 MM



General technical data:	
Type of voltage	AC/DC
Supply voltage frequency for auxiliary and control current circuit rated value	50 ... 60 Hz
Control supply voltage	
• at AC	
— at 50 Hz rated value	
— minimum	
— maximum	
— at 60 Hz rated value	
— minimum	
— maximum	
• at DC rated value	
— minimum	
— maximum	
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	0
Number of CO contacts for auxiliary contacts	1
Operating current of auxiliary contacts	

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX70041LB00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX70041LB00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX70041LB00&lang=en

last modified:

09.12.2015