

SURGE SUPPRESSOR VARISTOR WITH WIRE
SPACER AC 24 TO 48V/DC 24 TO 70V FOR
MOUNTING TO COIL TERMINAL FOR CONTACTORS
SIZE 0 TO 2




Figure similar

General technical data:		
Product designation		surge suppressor
Design of the surge suppressor		with varistor
Control circuit/ Control:		
Type of voltage of the control supply voltage		AC/DC
Control supply voltage frequency		
• 1 Rated value	Hz	50
• 2 Rated value	Hz	60
Control supply voltage 1		
• for DC		
— Initial rated value	V	24
— Final rated value	V	70
• with AC		
— at 50 Hz Initial rated value	V	24
— at 50 Hz Final rated value	V	48
— at 60 Hz Final rated value	V	48
— at 60 Hz Initial rated value	V	24
Certificates/ approvals:		



CSA



UR

[Confirmation](#)[Declaration of
Conformity](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/industrial-controls/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/industrymall>**Cax online generator**<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX74023G>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/3TX74023G>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX74023G&lang=en

last modified:

27.04.2015