





Busbar system, accessories Busbar center-to-center spacing 60 mm  
N/PE busbar holder for busbars 12x 5 (10)-30x 5 (10) and 6x 6 mm,  
free-standing installation or Attachment to 8US1923-2AA01



Model	
Product brand name	SENTRON
Design of the product	N/PE
Main circuit	
Operating voltage / at AC / rated value	690 V
Suitability for use	Flat bars
Type of connectable conductor cross-sections / for copper conductor / stranded	12 mm x 5 mm - 30 mm x 10 mm
Mechanical Design	
Busbar center-to-center spacing	60 mm

General Product Approval			Declaration of Conformity	Test Certificates	
 CSA	 UR		 EG-Konf.	<a href="#">Special Test Certificate</a>	<a href="#">Miscellaneous</a>

Shipping Approval	other
 PRS	 RINA
	<a href="#">Miscellaneous</a>

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1923-1AA01>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/8US1923-1AA01>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8US1923-1AA01](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1923-1AA01)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>