
SIEMENS

Data sheet 3RA6823-0AC



EXTENSION BLOCK 3FOLD, CONNECTION MAIN CIRCUIT: SPRING-LOADED TERMINAL, 3 SLOTS FOR COMPACT LOAD FEEDERS

General technical data:		
product brand name		SIRIUS
Product designation		3-expansion block
Protection class IP		IP20
Degree of pollution		3
Number of slots for compact feeder		3
Installation altitude at height above sea level maximum	m	2 000
Ambient temperature		
• during transport	°C	-55 ... +80
• during storage	°C	-55 ... +80
• during operation	°C	-20 ... +60
Vibration resistance		f = 4 to 5.8 Hz; d = 15 mm; f = 5.8 to 500 Hz; a = 2 m / s2 10 cycles
Shock resistance		Semi-sinusoidal a = 6 m/s2 at 10 ms; 3 pos. and 3 neg. Shock in all axes
Equipment marking acc. to DIN EN 61346-2		K
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750		K

Main circuit:		
Operating current with AC at 400 V Rated value	A	63
Operating voltage at AC-3 Rated value maximum	V	690

Installation/ mounting/ dimensions:		
Mounting type		screw and snap-on mounting
Width	mm	135

Changes preserved
© Copyright Siemens AG

Height	mm	197
Depth	mm	100

Connections/ Terminals:

Type of electrical connection for main current circuit		spring-loaded terminals
Wire stripping length for main contacts	mm	10
Connectable conductor cross-section for main contacts for load-side outgoing feeder		
• solid	mm²	1.5 ... 10
• stranded	mm²	1.5 ... 10
• finely stranded with core end processing	mm²	1.5 ... 6
• finely stranded without core end processing	mm²	1.5 ... 6
AWG number as coded connectable conductor cross section for main contacts for load-side outgoing feeder		14 ... 8
Type of connectable conductor cross-section for main contacts for load-side outgoing feeder		
• solid		2x (1.5 ... 6 mm²), 1x (1.5 ... 10 mm²)
• stranded		2x (1.5 ... 6 mm²), 1x (1.5 ... 10 mm²)
• finely stranded with core end processing		2 x (1.5 ... 6) mm²
• finely stranded without core end processing		2 x (1.5 ... 6) mm²
Type of connectable conductor cross-section for AWG conductors for main contacts for load-side outgoing feeder		2 x (16 ... 10), 1 x (16 ... 8)

Certificates/ approvals:

General Product Approval			EMC	Shipping Approval	
CSA	UL		C-TICK	BUREAU VERITAS	DNV

Shipping Approval				other	
LRS	PRS	RINA	RMRS	Declaration of Conformity	Environmental Confirmations

other

other

Changes preserved
© Copyright Siemens AG

Safety related data:

Protection against electrical shock		finger-safe

Further information


Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/industrial-controls/catalogs


Industry Mall (Online ordering system)
http://www.siemens.com/industrymall

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA68230AC

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RA68230AC

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA68230AC&lang=en





last modified: 27.04.2015

Changes preserved
© Copyright Siemens AG