

Busbar system Busbar center-to-center spacing 40 mm Device adapter, Width: 45 mm Bar thickness: 5+10 mm for motor feeders 3RV, 3RT1, 3RA with 1 DIN rail 35 mm, 25A Length 182 mm



Figure similar

Model	
Product brand name	SETRON
Product designation	Device adapter
Design of the product	Accessories
Current / at AC / rated value	25 A
Operating voltage / at AC / rated value	690 V
Width	45 mm
Busbar center-to-center spacing	40 mm
Net weight	157 g

General Product Approval	Declaration of Conformity	Test Certificates
--------------------------	---------------------------	-------------------



[Special Test Certificate](#)

[Miscellaneous](#)

Shipping Approval	other
-------------------	-------



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1051-5DM07>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1051-5DM07>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1051-5DM07

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



