

Busway Power Distribution

XL-X®, XL-U® and BD® Plug-In Units and Cubicles

Selection

Shipping Weights — Pounds

For Circuit Breaker Bus Plugs Only

Breaker Type	Ampere Rating	3-Phase, 3-Wire				3-Phase, 4-Wire			
		Enclosure Only		Complete Assembly		Enclosure Only		Complete Assembly	
		XL-U XL-X	BD, LO-X	XL-U XL-X	BD, LO-X	XL-U XL-X	BD, LO-X	XL-U XL-X	BD, LO-X
ED2, ED4, ED6	15–100	12	14	13	15	13	15	14	10
FD6, FXD	70–250	1	27	51	37	45	28	55	38

Fusible and Molded Case Circuit Breaker Cubicles

See page 15-7 for typical configurations.

Shipping Weights — Pounds

For Fusible Switch Bus Plugs Only

Switch Ampere Rating	3-Phase, 3-Wire		3-Phase, 4-Wire	
	XL-X XL-U	BD, LO-X	XL-X XL-U	BD, LO-X
	Prefix RV UV	Prefix BOS	Prefix RV UV	Prefix BOS
30,60	17	15	19	12
100	17	18	19	18
200	36	34	38	36

Special Bus Plugs

Description	Catalog Number		
	XL-U	XL-X	BD, LO-X
Ground Detector and Potentializer— For 2 or 3-pole 240 and 480 Volt service.	UPGR314G	RPGR314G	PGR6314

BD Bus Plug Catalog Number Reference

Catalog Number	ABD4 Busway						BDP4 Busway							
	225 ABD402	400 ABD404	600 ABD406	800 ABD408	1000 ABD410	1200 ABD412	225 BDP402	400 BDP404	600 BDP406	800 BDP408	1000 BDP410	1350 BDP413	1600 BDP416	
BOS16451	—	—	✓	—	✓	✓	—	—	—	—	—	✓	✓	
BOS16452	—	✓	—	✓	—	—	—	✓	✓	✓	✓	—	—	

As of June 2014, Siemens no longer supplies a complete solution for Legacy bus plug offerings.

15

BUSWAY SYSTEMS