



Electrically held lighting contactor
 20 Amp
 4NO / 0NC Poles
 Maximum voltage rating 600VAC
 Control voltage 110VAC 50HZ / 120VAC 60HZ
 NEMA Type 1 enclosure




Image is representative and may not depict the actual product.

General technical data:	
Weight	6 lb
Height x Width x Depth	11 x 7 x 5 in.
Finger-safe (main circuit / control circuit)	NA / NA
Maximum altitude	6560 ft
Ambient storage temperature	(-55 to 80)°C / (-67 to 176)°F
Ambient operating temperature	(0 to 40)°C / (32 to 104)°F
Humidity (% non-condensing)	10 to 95
Country of origin	USA
Contactor:	
Number of poles	4NO / 0NC
Mechanical operating cycles	30,000,000
Current ratings:	
Tungsten (poles per phase)	20A @277V 1p 1ph
	20A @480V 2p 1ph
	20A @480V 3p 3ph
Ballast (poles per phase)	20A @347V 1p 1ph
	20A @600V 2p 1ph
	20A @600V 3p 3ph
General & resistive (poles per phase)	20A @600V 1p 1ph
	20A @600V 2p 1ph
	20A @600V 3p 3ph
Internal/standard auxiliary contact:	
Number of NC / NO auxiliary contacts	0NC / 1NO
Rating	A600 / Q600
Optional auxiliary contact:	
Max number of NC / NO auxiliary contacts	4 max NC/NO combination
Rating	A300 / Q300
Coil:	
Voltage	110VAC 50HZ / 120VAC 60HZ Coil
Sealed watts	(no data)
Inrush / sealed power	31.7 / 4.8 VA
Normal coil operating limits (% of rated voltage)	85% - 110%
Typical drop-out volts (% of rated voltage)	(no data)
Pick-up time / Drop-out time	(no data)
Disconnect type (none):	
Rating	NA
Fuse type accepted	NA


Enclosure:	
Type	NEMA Type 1 enclosure
Rating	Indoor general purpose use
Mounting/wiring:	
Mounting orientation	Vertical
Mounting type	Surface
Line side connection type / torque	Screw / 7 - 12 lb-in
Line side solid & stranded conductors	2 x (20 - 16), 2 x (18 - 14), 2 x 12 AWG 75°C CU
Load side connection type / torque	Screw / 7 - 12 lb-in
Load side solid & stranded conductors	2 x (20 - 16), 2 x (18 - 14), 2 x 12 AWG 75°C CU
Coil connection type / torque	Screw / 7 - 10 lb in.
Coil solid & stranded conductors	2x(20-16), 2x(18-14) CU 75°C
Main auxiliary contact connection type / torque	Screw / 7 - 12 lb-in
Main auxiliary contact solid & stranded conductors	2 x (20 - 16), 2 x (18 - 14) AWG 75°C CU
Short circuit current rating:	
Fuses	100kA@600V (Class RK5 30A max)
Thermal magnetic circuit breaker	24kA@240V; 5kA@600V (25A max CB)
Additional information:	
Brochure	

OUTLINE 11x7x5 (SIZE 1) NEMA 1



LETTER	KNOCKOUT & CONDUIT SIZE
A	7/8" DIA. FOR 1/2" CONDUIT
B	7/8" X 1-1/8" DIA. FOR 1/2" & 3/4" CONDUIT
C	1-1/8" X 1-3/8" DIA. FOR 3/4" & 1" CONDUIT

DIMENSIONS ARE IN INCHES.
FILE NAME: SFS-D68870001-0211



LEN00B004 Wiring Diagram