


## Steel - Raintight

### Images



### Application

For maintaining wet locations seal on rated enclosures. Coated Washer installs on outside of 3R rated enclosure. Uncoated washer should be installed inside to maintain raceway continuity. Center reducing washers in middle of knock-out. Listed for use with Wet Location Connectors, or Threaded Rigid Conduit (and IMC) with standard locknuts. Patent Pending

### Product Information

Material: Galvanized Steel with EPDM Rubber Coating

### Certifications & Codes:

Federal Specification Number: A-A-50553  
NEMA Standard: FB-1  
UL File Number: E11259, cULus  
UL Standard: UL514B  
UNSPSC: 39121321

[Download Photo Image](#)   [Download Dimensional Image](#)  
Dimension A in Inches: 1.375  
Dimension B in Inches: 2.25  
Dimension C in Inches: 1.753

**Catalog ID:** 1066-RT

**UPC Number:** 78174714064

**Description:** Mighty-Seal® 1-1/4" to 1" Raintight Reducing Washers. Product contains one coated and one uncoated galvanized steel reducing washer. Maintains Raceway Integrity. Sunlight Resistant. Suitable for use in Wet Locations.

**Application:** For maintaining wet locations seal on rated enclosures. Coated Washer installs on outside of 3R rated enclosure. Uncoated washer should be installed inside to maintain raceway continuity. Center reducing washers in middle of knock-out. Listed for use with Wet Location Connectors, or Threaded Rigid Conduit (and IMC) with standard locknuts. Patent Pending

**Trade Size:** 1-1/4" - 1"

**Country of Manufacture:** USA

**Std Pkg Qty:** 200

**Unit Qty:** 20