


## Straight

### Images



[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 1.63

Dimension B in Inches: 1.98

Dimension C in Inches: 2.18

### Application

The CSS-075 is specially constructed for pour in place applications. The fitting flange end is designed to be mounted to a concrete form. The open end is then connected to the raceway. After the concrete has cured and the form is removed, the flange covering can then be punctured providing access to a threaded raceway entry point.

### Product Information

Material: High Strength Zinc Alloy

Finish: Ball Burnish

### Certifications & Codes:

Federal

Specification: A-A-50553A

Number:

NEMA

Standard: FB-1

UL File

Number:

UL

Standard:

UNSPSC: 39121311

CSS-075 Listed ETL: Bridgeport  
Fittings/CSS-075 Conforms to UL514B  
and CSA C22.2 No. 18.3

UL514B

**Catalog ID:** CSS-075

**UPC Number:** 78174792221

**Description:** 3/4" Rigid threaded concrete encasable flanged fitting

**Application:** The CSS-075 is specially constructed for pour in place applications. The fitting flange end is designed to be mounted to a concrete form. The open end is then connected to the raceway. After the concrete has cured and the form is removed, the flange covering can then be punctured providing access to a threaded raceway entry point.

**Trade Size:** 3/4"

**Std Pkg Qty:** 20

**Unit Qty:** 5