

# Product data sheet

## Characteristics

# 2510KS1

## Manual Switch - SS Flush - 2P - Toggle Operated - No Indicator - 600VAC

Product availability : Stock - Normally stocked in distribution facility



Price\* : 66.70 USD



### Main

Product or component type	Single Unit Manual Switch
Range of product	K

### Complementary

Line Rated Current	30 A
Motor power hp	3 hp at 460 V AC 2 hp at 230 V AC 2 hp at 115 V AC 3 hp at 575 V AC 1 hp at 90 V DC 2 hp at 115 V DC 1.5 hp at 230 V DC
System Voltage	600 V AC 230 V DC
Poles description	2P
Control type	Toggle
Phase	1 phase
Local signalling	No indicator
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
AWG gauge	AWG 14...AWG 10 (copper)
Height	4.5 in
Width	2.75 in
Depth	2.5 in

### Environment

Product certifications	UL listed file E42243 CCN NLRV CE
------------------------	--------------------------------------

NEMA degree of protection	Not rated (flush plate) stainless steel standard size
---------------------------	---

### Ordering and shipping details

Category	21102 - 2510,2511,2512 K
Discount Schedule	CP1
GTIN	00785901554653
Nbr. of units in pkg.	1
Package weight(Lbs)	0.4799999999999998
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

### Contractual warranty

Warranty period	18 months
-----------------	-----------