

Product availability : Stock - Normally stocked in distribution facility



Price* : 437.00 USD



Main

Range of product	9007
Series name	Heavy duty
Device short name	C
Head type	Turret head rotary lever
Material	Stainless steel
Type of operator	Maintained Spring return lever arm (to be ordered separately)
Switch actuation	CW and CCW
Cable entry	NPT conduit entry, cable outer diameter: 0.5 in
Contacts type and composition	1 NO/1 NC
Contact operation	Snap action

Complementary

Body material	Zinc alloy
Switch function	SPDT-DB
Contact form	Form Z
Contacts material	Silver alloy (Ag/Ni)
Minimum torque for tripping	3 lbf.in
Tripping angle	45 °
Maximum displacement angle	90 °
[Ie] rated operational current	10 A, Q600 10 A, A600
[Ui] rated insulation voltage	<= 600 V
Product certifications	CE CSA UL listed
Provided equipment	Receptacle

Environment

Ambient air temperature for operation	-20...185 °F
Environmental characteristic	Chemical pollution resistance

Ordering and shipping details

Category	21499 - 9007 C LIMIT SWITCHES
Discount Schedule	DS1
GTIN	00785901046059
Nbr. of units in pkg.	1
Package weight(Lbs)	1.25
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1150 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------