Product data sheet Characteristics

DTU324NRB SWITCH NONFUSIBLE DT 200A 3P NEUTRAL

Product availability: Stock - Normally stocked in distribution facility



Price*: 3005.00 USD



Main

Product or component type	Double Throw Safety Switch
Line Rated Current	200 A
Product certifications	UL listed
NEMA degree of protection	NEMA 3R galvannealed steel
Device composition	Neutral (factory installed)
Disconnector device type	Non-fusible disconnect
Device mounting	Surface
Number of poles	3
System Voltage	240 V AC
ANA/O	250 V DC
AWG gauge	AWG 6300 kcmil (copper or aluminium)

Ordering and shipping details

Main		
Product or component type	Double Throw Safety Switch	
Line Rated Current	200 A	
Product certifications	UL listed	
NEMA degree of protection	NEMA 3R galvannealed steel	
Device composition	Neutral (factory installed)	
Disconnector device type	Non-fusible disconnect	
Device mounting	Surface	
Number of poles	3	
System Voltage	240 V AC 250 V DC	
AWG gauge	AWG 6300 kcmil (copper or aluminium)	
Ordering and shipping details		
Category	00133 - DT SWITCH,NEMA3R	
Discount Schedule	DE1	
GTIN	00785901185901	
Nbr. of units in pkg.	1	
Package weight(Lbs)	81.96000000000008	
Returnability	Υ	
Country of origin	US	
Offer Sustainability		
O attack to a first at	Not Once Book' mondert	

Offer Sustainability

Sustainable offer status	Not Green Premium product	entati
RoHS (date code: YYWW)	Compliant - since 1313 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	his do
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	sclain

Warranty period

18 months