

Product availability : Stock - Normally stocked in distribution facility



Price* : 1010.00 USD



Main

Range	TeSys
Product name	TeSys LK
Product or component type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch
Suitability for isolation	Yes

Complementary

Poles description	3P
Network type	AC DC
Network frequency	50/60 Hz
[Ie] rated operational current	200 A conforming to CSA 200 A conforming to UL 200 A (AC-22A) at 400 V AC conforming to IEC 200 A (AC-23A) at 400 V AC conforming to IEC 200 A (AC-22A) at 690 V AC conforming to IEC 200 A (AC-23A) at 690 V AC conforming to IEC
System Voltage	600 V AC 50/60 Hz
[Ui] rated insulation voltage	750 V
Control type	Rotary handle
Type of operating handle	External frontal External right side
Mounting support	Plate
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC
Rated power in W	100 kW at 400 V 140 kW at 500 V 185 kW at 690 V
Rated power in hp	75 hp at 240 V 92 A AC 150 hp at 480 V 187 A AC 200 hp at 600 V 192 A AC 15 hp at 125 V 112 A DC

15 hp at 250 V 56 A DC

[Icw] rated short-time withstand current	32 kA
Mechanical durability	8000 cycles
Electrical durability	6000 cycles
Connections - terminals	Lugs-ring terminals 1 cable(s) 16 mm ²
Height	6.3 in (160 mm)
Width	7.09 in (180 mm)
Depth	3.74 in (95 mm)

Environment

Standards	IEC 60947-3 CSA C22.2 No 4 UL98
Product certifications	CE CSA UL

Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	00785901546306
Nbr. of units in pkg.	1
Package weight(Lbs)	5.020000000000005
Returnability	Y
Country of origin	FR

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0844 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------