# Product data sheet Characteristics

# XB5RFA02

# Pack 22mm XB5R programble receiver AC/DC

Product availability: Stock - Normally stocked in distribution facility





#### Main

		,
Range of product	Harmony XB5R	,
Product or component type	Wireless and batteryless package	y y
Device short name	XB5R	
Head material	Plastic	
Kit composition	1 plastic push-button, 1 receiver and 1 set of caps	# Jo
Transmission frequency	2405 MHz for transmitter 2405 MHz for receiver	in the land
Level or class	5M00G7W	ō <u>≧</u>
Antenna type	Omnidirectional	<u>.</u> <u>.</u>
Device composition	ZB5RZA0 ZBRRA ZB5AZ009 ZBRT1 ZBA79	ed for determining s

## Complementary

Wireless and batteryless push-button Ø 22 mm assembled on fixing collar	<u>2</u> . <u> </u>
Programmable receiver (2 relays)	
24240 V AC/DC 50/60 Hz	g :=
1 LED green power ON 2 LEDs green relay ON 2 LEDs green function mode 1 LED green and yellow reception signal	ماناه م
Zigbee conforming to IEEE 802.15.4	<u>.</u>
<= 1 mW	. <u></u>
1	
O-QPSK	
5 MHz	
0 dBi	<u>:</u> ا ا
	Programmable receiver (2 relays)  24240 V AC/DC 50/60 Hz  1 LED green power ON 2 LEDs green relay ON 2 LEDs green function mode 1 LED green and yellow reception signal  Zigbee conforming to IEEE 802.15.4  <= 1 mW  1  O-QPSK 5 MHz

## Environment

Product certifications	C-Tick
	CSA
	GOST
	CCC
	UL
Marking	CE
Standards	EN/IEC 60947-5-1
	CSA C22.2 No 14
	UL 508
	EN/IEC 60947-1
Radio agreement	FCC
	ICASA
	SRRC
	ARIB T66
	ANATEL
	RSS

#### Ordering and shipping details

ordorning and oripping dotailo	
Category	22470 - XB5R WIRELESS PUSH BUTTON
Discount Schedule	I
GTIN	00785901939597
Nbr. of units in pkg.	1
Package weight(Lbs)	0.510000000000001
Returnability	Υ
Country of origin	FR

## Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1021 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Available	

#### Contractual warranty

Contraction Warranty		
Warranty period	18 months	