




401 Clevis Hanger – 4011200HD



- Recommended for the suspension of stationary non-insulated pipe lines
- Flared edges help prevent sharp surfaces from coming into contact with the pipe (1/2" to 2" pipe sizes)
- Clevis bottom pivots to allow pipe to be fed from either direction
- Conforms with U.S. Federal Specification WW-H-171 (Type 1), Manufacturers Standardization Society (MSS) SP-58 (Type 1)



Part Number	4011200HD
Material	Steel
Finish	Hot-Dip Galvanized
Pipe Size	12"
Outer Diameter (OD)	12 3/4"
Rod Size (RS)	7/8"
A	18 5/8"
B	10 3/16"
C	3 1/16"
Static Load (F)	3,800 lb
Standard Packaging Quantity	1 pc
UPC	78285658224
EAN-13	8711893090529

A shield is recommended for insulated pipe applications to effectively distribute the load.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

