




CADDY MACROFIX PLUS LF Low-Friction – 4300125EG



- Includes easy closing mechanism
- Age resistant lining designed specifically for plastic pipe applications
- Low-friction properties allow for expansion, contraction and easy sliding of pipe
- Conforms with Manufacturers Standardization Society (MSS) SP-58 (Type 12)
- Category II noise reduction according to DIN EN ISO 3822-1
- Compliant for sound insulation design according to DIN 4109



Part Number	4300125EG
Material	Steel EPDM-SBR Rubber
Finish	Electrogalvanized
Color	Green
Temperature	-58 to 230 °F
Outer Diameter (OD)	1.575"
Pipe Size	1 1/4"
Plastic Pipe Size	40 mm
Rod Size (RS)	3/8"
Width (W)	1 3/16"
Thickness (T)	1/16"
Static Load (F)	250 lb
Standard Packaging Quantity	50 pc
UPC	78285665776

Lining is EPDM rubber.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

