


# CADDY CAT HP J-Hook with Pin Driven Angle Bracket – CAT48HPAFAB3



- Longer leg angle bracket for tool clearance
- Designed to fit a variety of pin drivers
- Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic
- Provides superior fill capacity and load rating over most other non-continuous cable support alternatives
- Rounded edges on J-Hooks provide proper bend radius support for high performance data cables
- Cost effective alternative to expensive cable tray
- Complies with EN 50174-2
- Meets ISO®/IEC 14763-2, ANSI®/TIA 568 and ANSI®/TIA 569



|                             |                                                         |
|-----------------------------|---------------------------------------------------------|
| Part Number                 | CAT48HPAFAB3                                            |
| Material                    | Steel                                                   |
| Finish                      | Pregalvanized                                           |
| Diameter (Ø)                | 3"                                                      |
| Area                        | 9.26 in <sup>2</sup>                                    |
| Cable Capacity, Cat 5e      | 200                                                     |
| Cable Capacity, Cat 6       | 150                                                     |
| Cable Capacity, Cat 6A      | 80                                                      |
| Hole Size (HS)              | 3/16"                                                   |
| Static Load (F)             | 60 lb                                                   |
| Certifications              | cULus<br>DIN 4102-12 abP P-3117/339/14-MPA BS (Germany) |
| Standard Packaging Quantity | 25 pc                                                   |
| UPC                         | 78285680321                                             |
| EAN-13                      | 8711893136258                                           |

Non-continuous supports may not exceed spacing of 5' (1.5 m) per TIA 569-C.9.7 and EN 50174-2.  
Cable capacity is calculated based on a 70% fill rate.



ANSI is a registered trademark of American National Standards Institute. ISO is a registered trademark of International Organization for Standardization. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

