


CADDY CAT HP J-Hook Tree, Wall Mount – CAT64HPSWM3



- Ideal for attaching to concrete, steel or wood surfaces
- Provides optimal support for high-performance data cable, up to and including Cat 5e, Cat 6, Cat 6A, Cat 7 and fibre optic
- Ready to use out of the box, saving installation time and labor
- Requires no screws, rivets or special tools for assembly
- Provides superior fill capacity and load rating over most other non-continuous cable support alternatives
- Complies with EN 50174-2
- Meets ISO®/IEC 14763-2, ANSI®/TIA 568 and ANSI®/TIA 569



Part Number	CAT64HPSWM3
Material	Steel
Finish	Pregalvanized
Type	Single Sided
Diameter (Ø)	4"
Tiers	3
Height (H)	27"
Depth (D)	5 1/2"
Width (W)	2"
Hole Size (HS)	1/4"
Static Load (F)	180 lb
Standard Packaging Quantity	5 pc
UPC	78285679923
EAN-13	8711893136913

Static loads represent maximum load limit of J-Hook tree. Static load limit of each J-Hook is 60 lb [270 N].
Non-continuous supports may not exceed spacing of 5' [1.5 m] per TIA 569-C.9.7 and EN 50174-2.



ANSI is a registered trademark of American National Standards Institute. ISO is a registered trademark of International Organization for Standardization.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

