





CADDY SPEED LINK SLS with Threaded Stud End – SLS2L5SE250



- Complete system includes wire, locking device and pre-assembled threaded stud end fitting
- Attaches to structures with threaded anchors or devices with threaded hole



Part Number	SLS2L5SE250
Material	Steel Polypropylene Zinc Alloy
Finish	Electrogalvanized
Static Load Safety Factor	5:1
Complies With	SMACNA HVAC-DCS
Wire Rope Diameter	2 mm
Wire Rope Length	16.4'
Rod Size (RS)	1/4"
Screw Length (L)	1"
Static Load (F)	60 lb
Thread Size (TS)	M8
Height 1 (H1)	2.1"
Height 2 (H2)	1.7"
Width (W)	0.63"
Thickness (T)	0.15" Max
Hole Size (HS)	0.31" – 0.38"
Slot Size (SS)	0.31" x 0.25" - 0.31" x 0.38"
Standard Packaging Quantity	10 pc
UPC	78285692713

The 2 mm locking device is compatible with C-Channel Types E0 and E0L.
Total load per wire on a multi-tier trapeze must not exceed static load.



WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

