



Catalog Number: U5300-O-75-L
Item Description: 125A RT MTR DB PED
UPC Code: 784572258495

Brand Name: Milbank

Type: Ring Type Metered Power Supply Unit

Special Features: 4 Terminal, Plain Top, 2 Barrel Ground Lug and Ground Bar, No Bypass, Single Power Head, 6 Branch Circuits, Light Kit

Application: RV Power

Standard: UL Listed

Voltage Rating: Up to 240 Volts Alternating Current

Amperage Rating: 125 Ampere Continuous

Wattage: Not Applicable

Frequency Rating: 60 Hertz

Phase: 1 Phase

Number of Receptacles: 3

Receptacle Configuration: NEMA 14-50, NEMA TT30, NEMA 5-20 Ground Fault Receptacle

Control: Single Pole 20 Ampere Breaker, Single Pole 30 Ampere Breaker, Double Pole 50 Ampere Breaker, No Main Breaker

Material: G90 Galvanized Steel with Powder Coat Finish

Mounting: Pedestal Mount

Cable Size: 6 AWG to 350 KCMIL

Enclosure: Type 3R



Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.