



Catalog Number: U5796-X-400-CB  
Item Description: 320A COLD 7T 3P4W OH  
UPC Code: 784572478992



Brand Name: Milbank  
Type: Ringless Meter Socket  
Application: Meter Socket With Main  
Standard: UL Listed  
Voltage Rating: Up to 600 Volts Alternating Current  
Amperage Rating: 320 Continuous Ampere  
Phase: 3 Phase  
Frequency Rating: 60 Hertz  
Number Of Cutouts: 1  
Cutout Size: 400 Ampere Main Breaker  
Cable Entry: Overhead  
Terminal: Single Mechanical Line Side and Single Mechanical Load Side  
Mounting: Surface Mount  
Enclosure: Type 3R, G90 Galvanized Steel with Powder Coat Finish

Additional Specifications: Number of Jaws:7 Terminal  
Hub Opening and Closing Plates:Large Closing Plate  
Hub Opening and Closing Plates:Large Closing Plate  
Hub Opening and Closing Plates:Large Closing Plate  
Hub Opening and Closing Plates:Large Closing Plate  
Hub Opening and Closing Plates:Large Closing Plate



*Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.*

| FEATURE TABLE |     |                          |
|---------------|-----|--------------------------|
| ITEM          | QTY | DESCRIPTION              |
| A             | 5   | U/L MNTG.EMBOSS          |
| B             | 1   | ¼ SOLID K.O.             |
| C             | 1   | ¼, ½ CONC. K.O.          |
| D             | 2   | 1¼, 1½, 2, 2½ CONC. K.O. |
| E             | 6   | 3, 3½, 4 CONC. K.O.      |



Version:

1

All dimensions are +/- 1/16".  
Drawing views are not to scale.  
Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.