



Catalog Number: U5230-XL-76GR
Item Description: 125A UNMET DBL PDMT PED
UPC Code: 784572497399

Brand Name: Milbank

Type: Unmetered Power Supply Unit

Special Features: Small Closing Plate, 2 Barrel Ground Lug and Ground Bar, No Bypass, Double Power Head, 6 Branch Circuits

Application: RV Power

Standard: UL Listed

Voltage Rating: Up to 240 Volts Alternating Current

Amperage Rating: 125 Ampere Continuous

Wattage: Not Applicable

Frequency Rating: 60 Hertz

Phase: 1 Phase

Number of Receptacles: 3

Receptacle Configuration: Two NEMA 5-20 Ground Fault Receptacles, NEMA 14-50

Control: Two Single Pole 20 Ampere Breakers, One Double Pole 50 Ampere Breaker, No Main Breaker

Material: G90 Galvanized Steel with Powder Coat Finish

Mounting: Pedestal Mount





Cable Size: 6 AWG to 350 KCMIL

Enclosure: Type 3R



Utility requirements may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must always be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.

FEATURE TABLE		
ITEM	QTY	DESCRIPTION
A	6	U/L MNTG.EMBOSS
B	2	¼ SOLID K.O.
C	4	½, ¾, 1, 1¼ CONC. K.O.
D	2	½, ¾, 1, 1¼, 1½ CONC. K.O.
E	1	¾, 1, 1¼, 1½, 2 CONC. K.O.



Version:

1

All dimensions are +/- 1/16".
 Drawing views are not to scale.
 Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.